

Eddie Baza Calvo
Governor



Anthony C. Blaz
Director, Dept. of Admin.

GENERAL SERVICES AGENCY
Government of Guam
148 Route 1 Marine Drive Corp
Piti, Guam 96915

Ray Tenorio
Lt. Governor

November 12, 2015

Invitation for Bid GSA/PAG-020-15

ARTICULATING, TELESCOPIC BOOM LIFT 40' REACH; 2WD/ 120'REACH; 4WD

Amendment # 3

1. Amend to replace Pages 28 and 29 of 31 to read as follows:
"Revised Page 28 of 31 dated 11/12/2015 and Revised Page 29 of 31 dated 11/12/2015".
2. Revised Pages 28 and 29 of 31 are attached with this Amendment.

All others remain unchanged.

A handwritten signature in black ink, appearing to read 'Claudia S. Acfalle', written over a horizontal line.

Claudia S. Acfalle
Chief Procurement Officer

ITEM NO.	DESCRIPTION	QTY	UNIT	UNIT PRICE	PRICE EXTENSION
1.1	Articulating, Telescopic Boom Lift 40' reach; 2WD as per the	1	EA.	\$	\$

Following specifications:

SPECIFICATIONS:

BIDDING AND OR REMARKS:

Engine:	38 hp minimum, Diesel Engine. Engine shutoff protection system (Low Oil Pressure, High Hydraulic Oil Temperature)	_____
Fuel Type:	Diesel (Ultra Low Sulfur) Tier IV	_____
Fuel Tank:	The fuel tank furnished shall be Min. of 14 gallons and Max of 30 gallons.	_____
Platform Reach:	40 feet	_____
Platform Dimensions:	30 x 90 with railing	_____
Lift Capacity:	500 lbs	_____
Platform Rotation:	180 degrees	_____
Swing:	360 degrees continuous	_____
Steering:	Selectable Steering (ground level or platform)	_____
Gauges:	Air, Fuel, Hour, Volt, Temp, and Oil	_____
Lights:	2 Headlights in facing forward with protective guard, 2 Headlights facing rear with protective guard. 2 work lights on platform	_____
Tires:	Protector Lug Foam Filled tires	_____
Manlift Accessories:	Hostile Weather/Environment Kit AC plug/outlet in platform Standard manufacture accessories' to include Horn, Electric Amber strobe light, key switch "on position" activated. Mounted 5 lbs. fire extinguisher on platform 1 set "Shop Type" repair manuals and complete illustrated Parts manual. Diagnostic and Troubleshooting software Owner/Operator manual for each equipment Maintenance and Service manual for each equipment Warranty booklet for each equipment All fluids to the fullest level Fuel tank to be loaded with 10 gallons of diesel. Electronic Backup alarm Engine shut-off protection system (Low Oil Pressure, High Engine Temperature and High Transmission Temperatures), 1 each full set tire and rim assemble per size, Foam Fill Reflective Conspicuity Tape Electronic rust prevention system	_____ _____
Receiving Date:	(Acceptance Date) will be Three (3) days after delivery date, Provided the Equipment is Delivered Completely assembled and Meets all specifications, terms and conditions of the bid Requirements.	_____ _____ _____
Special Provision:	If parts catalog and maintenance repair comes in CD-ROM or Micro-Fiche, bidder must supply to requesting agency. Bidder must still Provide hard (book) copy to the requesting agency.	_____ _____ _____

Training: Provide 2 sessions on pre inspection, post inspection and safe Operational procedures for all operators, leaders, supervisors, And dispatchers within Maintenance Division.

Bidding on : **Articulating, Telescopic Boom Lift 40' reach, 2WD**

MANUFACTURER: _____
MAKE: _____
MODEL: _____
YEAR: _____
PLACE OF ORIGIN: _____
DATE OF DELIVERY: _____

2.1 Articulating, Telescopic Boom Lift 120' reach, 4WD as per the Following specifications: 1 EA. \$ _____ \$ _____

SPECIFICATIONS:

BIDDING AND OR REMARKS:

Engine:	74 hp minimum, Diesel Engine Engine shutoff protection system (Low Oil Pressure, High Hydraulic Oil Temperature)	_____
Fuel Type:	Diesel (Ultra Low Sulfur) Tier IV	_____
Fuel Tank:	The fuel tank furnished shall be Min. 30 gallon	_____
Platform Reach:	120 ft & 8 ft jib	_____
Platform Dimensions:	36 x 96 with railing	_____
Platform Capacity:	Unrestricted - 1000 lbs Restricted - 500 lbs	_____
Platform Rotation:	180 degrees	_____
Swing:	360 degrees continuous	_____
Steering:	Selectable Steering (ground level or platform)	_____
Axles:	Extendable front and rear	_____
Gauges:	Air, Fuel, Hour, Volt, Temp, and Oil	_____
Lights:	2 Headlights in facing forward with protective guard, 2 Headlights facing rear with protective guard. 2 work lights on platform	_____ _____ _____
Tires:	Protector Lug Foam Filled tires	_____
Manlift Accessories:	Platform to be plumbed with air lines for use of pneumatic tools. Hostile Weather/Environment Kit AC plug/outlet in platform Standard manufacture accessories' to include Horn, Electric Amber strobe light, key switch "on position" activated. Mounted 5 lbs. fire extinguisher on platform 1 set "Shop Type" repair manuals and complete illustrated parts Manual. Diagnostic and Troubleshooting software Owner/Operator manual for each equipment Maintenance and Service manual for each equipment Warranty booklet for each equipment Recommended spare parts list All fluids to the fullest level Fuel tank to be loaded with 10 gallons of diesel. Electronic Backup alarm	_____ _____